



Dual-channel In-ceiling Loudspeaker

Applications:

The A-815D combines the performance of the A-815 with the convenience of a dual-channel design. Dual voice coils and dual 1-inch swivel tweeters provide high fidelity and stereo sound in a single, easy to install, flush-trim design. The A-815D is perfect for rooms and locations requiring both left and right stereo channels from a single speaker and a full, deep, rich sound.

Technical Information:

Model Name/Number: A-815D

Primary Use: In-ceiling **Series:** A Series

System Type: 2-way In-ceiling

Frequency Response: 50Hz — 20kHz ± 3dB

Sensitivity: 90dB (2.83 Volts @ 1 Meter)
Recommended Power: 50-100 Watts x 2 channels

Drive Units: (1) 8" PolyGraphite Cone Woofer

(1) 1" Silk Dome Tweeters

Tweeter Protection: Yes
Swivel Tweeter: Yes (2)
Crossover Frequency: 2500 Hz
Crossover Slope: 12dB/Octave
Impedance: 8 0hms

Color: White ABS (paintable)

Grille: White Aluminum (paintable)

Installation Bracket: Included
New Construction Bracket: NCB-8R*
Rear Enclosure: BC-8R*

Finished Dimensions: 103/4" Dia. x 43/4" D

Cut-out Dimensions: 9½" Dia.

Weight: 6 Lbs.

Warranty: 25 Years**

*Sold Separately

**Warranted for 25 (twenty five) years from date of purchase to be free from
defects and workmanship. For more information see your RBH dealer.



Frequency Response Graph:

