T-2 TOWER MODULAR SPEAKER



ТМ

The T-2 consists of a T-1 atop a 1010-SEN subwoofer. As a mirror-image pair, the T-2 excels in providing the most discriminating listener with an amazing aural experience. The T-2 is capable of handling large amounts of power while delivering the highest fidelity and performance in even the largest home theater or listening room. The image-focusing driver alignment and clarity of the T-1 mated with the 1010-SEN's phenomenal bass deployment make the T-2 among the best performing freestanding speakers RBH Sound has ever produced. Shown here in South American rosewood veneer finish.



REDEFINING THE WAY YOU EXPERIENCE SOUND.™

382 Marshall Way, Layton, Utah • USA • 84041 • Toll Free: (800) 543-2205 • Fax: (801) 543-3300 • www.rbhsound.com It is RBH Sound policy to continuously incorporate improvements into products; all specifications are subject to change without notice. Copyright © 2010 RBH Sound. All Rights Reserved.

SPECIFICATIONS

MODEL NAME: T-2

SYSTEM TYPE: Tower Modular Speaker

SERIES Signature Series T Systems

FREQUENCY RESPONSE 20Hz — 20kHz ± 3dB

SENSITIVITY 92dB (2.83 Volts @ 1 Meter)

RECOMMENDED POWER 100-1000 Watts

DRIVE UNITS (2) 10" (254mm) Aluminum Subwoofers (4) 6¹/₂" (165mm) Aluminum Woofers (3) 1" (25mm) Silk Dome Tweeters

611/4"

-131/4"

FRONT VIEW

T-1 or T-1/R-

→ | ◄

T-2N or T-2N/R -

18"

SIDE VIEW

CROSSOVER FREQUENCY 2,500 Hz

CROSSOVER 24dB/Octave

IMPEDANCE

4 Ohms

CABINET

Black Oak Wood Grain with Gloss Top and Base or 30 Different Real Wood Finishes

GRILLE

Black Cloth

DIMENSIONS

13¼″ W x 61¼″ H x 18″ D (337mm W x 1556mm H x 457mm D)

WEIGHT

140 lbs. (63.50 kg)

WARRANTY

5 Years*

*Warranted for 5 (five) years from date of purchase to be free from defects and workmanship. For more information see your RBH dealer.




High Performance Home Audio Redefining the Way You Experience Sound™



DIMENSIONS & CONFIGURATIONS

The mid-range and bass drive units of the T System are of the highest quality and feature cutting-edge aluminum cone technology. The two 10-inch long-throw subwoofers deliver plentiful amounts of low frequency information. Mid-bass through lower treble frequencies are accurately reproduced through four 6¹/₂-inch woofers offering extended dynamic range and lower distortion. Three 1-inch silk dome high performance tweeters provide generous crystal clear high frequencies with unbelievable detail and accuracy. The woofers and tweeters are arranged in a dispersionaveraging alignment that focuses the sound at the listening position for unbelievable imaging. Working in harmony, all drive units are governed by an extensive filter network to convey the sonic realism you'd expect from this reference-grade speaker system.



T-2N or T-2N/R:	,	T-3N or T-3N/R:	2 each T-1 or T-1/R Modular Speakers 4 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 4 sets of T-Module Clamps 2 sets of T-Module Feet
T-2P or T-2P/R:	2 each T-1 or T-1/R Modular Speakers 2 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 2 each SA-400 Subwoofer Amplifiers 2 sets of T-Module Clamps 2 sets of T-Module Feet	T-3P or T-3P/R:	2 each T-1 or T-1/R Modular Speakers 4 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 4 each SA-400 Subwoofer Amplifiers 4 sets of T-Module Clamps 2 sets of T-Module Feet

T-2P or T-2P/R -

Specifications are subject to change. For the most current information visit us online at www.rbhsound.com.