RS10i POWERED SUBWOOFER



THIS PRODUCT WAS DISCONTINUED SEPTEMBER 2014

The RS10i powered subwoofer has its own source of amplification, and a variable crossover, adjustable pahse control and auto on/off are also used for convenience and easy integration with other speakers. Audio can be supplied to the subwoofer by either interconnect (processor/line level). The 10-inch poly-matrix cone woofer enhances bass definition and accuracy. A built in limiter protects the subwoofer from being over driven and bottoming out. Available in high-gloss red burl.

SPECIFICATIONS

Model Name: RS10i

Series: Impression
System Type: Digital Class D
Frequency Response: 35Hz-150Hz (±3dB)

Voltage: 110V/220V Amplifier Power: 250 Watts RMS

Drive Units: (1) 10" (254mm) Poly-matrix Cone Subwoofer

Crossover: 40Hz-150Hz (continuously variable)

Line Level Input: Yes
Speaker Level Inputs: Yes
Speaker Level Outputs: Yes

Phase Controls: Yes (0/180 Degrees)

Cabinet Finish: Available in High-gloss Red Burl Dimensions: 14-1/8" W x 15" H x 16-1/4" D

(359mm W x 381mm H x 413mm D)

Weight: 27 lbs. (12.25 kg) Warranty: 5 Years/1 Year*